

# Product Safety Data Sheet

**XEROX**

**Product:** Phaser 1235

**PSDS No.:** 0859  
**ISSUE DATE:** 10/27/00  
**REV. DATE:**

## Section I - Product Identification

**Manufacturer's Name**  
Xerox Corporation

**Emergency No.**  
(716) 422-2177

**Manufacturer's Address**  
Rochester, N.Y.

**Product Designation**  
Phaser 1235

**Product Identifier:**  
YSA-1

## Section II - Electrical Information

<b>Line Voltage</b> (Volts)	<b>Line Current</b> (Amps)	<b>Freq.</b> (Hertz)
115	13.0	60

**Branch Cir. Protection**  
(Amps)  
20

**Line Cord/Plug Specification**  
Equipped with Appliance coupler  
Detachable Cord, Two wire + Ground  
NEMA 5-15P/ -20P

**Power Consumption(Watts)\***  
  
Running: 381  
Standby: 113

**Agency Approval**  
**UL** File Number E51242  
**cUL** File Number E51242

## Section III - Supplies

	<b>Xerox Part No.</b>	<b>Material Safety Data Sheet</b>
CRU TONER	6R90303, 6R90304, 6R90305, 6R90306	A-0617, A-0618, A-0619, A-0620
CRU DRUM	6R90293, 6R90294, 6R90295, 6R90296 13R90132, 13R90133, 13R90134, 13R90135	

## Section IV - Environmental Information

<b>Product Size</b> (Centimeters / Inches)	<b>Heat Emission*</b> (BTU/HR)	<b>Environmental Limitations</b>	
		<b>Min</b>	<b>Max</b>
D: 62 / 24.4	Running: 1,295	Relative Humidity (%)	15 85
W: 43 / 16.9	Standby: 384	Ambient Temp. (°C)	10 32
H: 43 / 16.9			

**Floor Space Requirements**  
(Meters / Feet)  
N/A - Desktop unit

**Weight**  
(K Grams / Lbs.)  
IOT 51 / 113

\* Based on a five minute average

\*\* MSDS is not required by OSHA, Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2) )

Section V - Emission/Exposure Information\*

**Light Source**

LEDs

**Electromagnetic Emissions**

US FCC: Class B

Canada DOC: Class B

**Audible Noise**

Run 66.0 dB(A)

Standby 55.0 dB(A)

Impulse 73.0 dB(A)

**TLV**

85.0 dB(A)

**Ozone**

Concentration Based on Simulation Model:

Daily Copy Volume 136 copies/ hours

Room Size 8 m<sup>3</sup>

1/2 Air Room Change per Hour

0.003 ppm (TWA)

**TLV**

0.1 ppm

**Total Dust**

0.13 mg/m<sup>3</sup>

**TLV**

10 mg/m<sup>3</sup>

\* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time-Weighted Average) for a normal eight-hour workday.

10/27/00